



Health	3
Fire	3
Reactivity	1
PPE	G









Product Name: Covaron InfernoWare™ Shield SN14 **Application:** Thermosetting amorphous ceramic compound

CAS#: Not available RTECS: Not available

Document Revision: 1.3

Document Revision Date: 2024 June 19

Supplier Information: 1-734-315-4221

Covaron Advanced Materials 4401 Varsity Dr, Suite A Ann Arbor, MI 48108

CHEMTREC (24-hour): 1-800-424-9300
Poison Control (24-hour): 1-800-222-1222
For non-emergency assistance: 1-734-315-4221

SECTION 2: HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910 (OSHA HCS)

.Physical, Flammable Liquids, 3

In contact with water release flammable gas

.Health, Acute toxicity, 5 Oral

. Health, Specific target organ toxicity-Single $\,$

Exposure, 3

Skin Corrosion 1A Skin Sensitization 1 Serious Eye damage 1

Signal word

Danger

HAZARDS IDENTIFICATION				
GHS haz	GHS hazard statements			
H225	Highly flammable liquid and vapor			
H261	In contact with water release flammable gas			
H302	Harmful if swallowed			
H312	Harmful in contact with skin			
H315	Cause skin irritation			
	May cause an allergic skin reaction			
H334	Respiratory sensitization			
H336	May cause drowsiness or dizziness			
GHS pre	cautionary statements			
P201	Obtain special instructions before use.			
P202	Do not handle before reading and understanding safety			
	precautions.			
P210	Keep away from heat, sparks, open flames and hot			
	surfaces. No smoking.			
P232	Protect from Moisture.			
P233	Keep container tightly closed. Keep cool.			
P235				
P240	Ground and bond container and receiving equipment.			
P241	Use explosion-proof electrical, ventilating, lighting and			
	mixing equipment.			
P242	Use only non-sparking tool.			
P243	Take precautionary measures against static discharge.			
P261	Avoid breathing fumes, mist, and vapor.			
P264	Wash skin thoroughly after handling.			
P270	Do not eat, drink or smoke when using this product.			

	P271	Use only outdoors or in a well-ventilated area.
	P272	Contaminated work clothing must not be allowed out
		of the workplace.
	P280	Wear protective gloves/protective clothing/eye
		protection/face protection.
	P284	Wear respiratory protection.
	P301	IF SWALLOWED: Call a POISON CENTER/doctor if you
	P312	feel unwell. Rinse mouth. Do NOT induce vomiting.
	P330	-
	P331	
	P303	IF ON SKIN (or hair): remove immediately all
	P361	contaminated clothing. Rinse skin with water or
	P353	shower.
	P304	IF INHALED: Remove victim to fresh air and keep at rest
	P340	in a position comfortable for breathing. Call a POISON
	P312	CENTER or doctor if you feel unwell.
	P305	IF IN EYES: Rinse cautiously with water for several
	P338	minutes. Remove contact lenses, if present and easy to
	P351	do. Continue rinsing. Immediately call a POISON
		CENTER/doctor.
	P314	Get medical advice/attention if you feel unwell.
	P333	If skin irritation or rash occurs: Get medical
	P313	advice/attention.
	P363	Wash contaminated clothing before use.
	P370	In case of fire: Use only dry chemical or carbon dioxide
	P378	for extinction.
	P403	Store locked up in a well-ventilated place.
	P405	
<u> </u>	P501	Dispose of contents and containers to an approved
		facility in accordance with local, regional, national, and
		international regulations.

ame	CAS#	Wt%
uminum oxide	1344-28-1	0-10
narcoal	16291-96-6	0-5
on oxide	1309-37-1	0-8
prietary ceramic and/or metallic	_	5-45
ment		
oprietary	_	5-40
achlorobenzotrifluoride	98-56-6	20-65
anol	75-21-8	0-30

SECTION 4: FIRST AID MEASURES

General advice	Consult a physician. Provide this data sheet to medical personnel. Move out of dangerous area.
If inhaled	Move person to fresh air. Seek medical attention. If not breathing or unconscious, provide artificial respiration. Exercise caution if performing mouth-to-mouth resuscitation for persons who have inhaled toxic or caustic substances.
Skin Contact	Immediately flush skin with large amount of water while removing contaminated clothing and shoes. Wash off with soap and water for at least 15 minutes. If symptoms persist, seek medical attention. Do not peel solidified product off the skin.
Eye Contact	Rinse thoroughly with plenty of water or saline solution for at least 15 minutes, occasionally lifting the upper and lower lid. Remove contact lenses if present and easy to do. Continue rinsing. Consult a physician.
Ingestion	Do not induce vomiting. Vomiting may occur spontaneously. To prevent aspiration of material into the lungs, lay the victim on one side with head lower than the waist. Never give anything by mouth to an unconscious person. Rinse mouth with water, then drink a lot of water. Remove denture if present. Seek medical advice.

Extinguishing media	Suitable methods of extinction: Use only dry chemical or carbon dioxide. Unsuitable methods of extinction: Water jets streams may spread the fire.
Special hazards	Flammable liquid and vapor! Vapors are heavier than air and can travel along the ground to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas. Liquid will float and may reignite on the surface of water.
Advice for firefighters	Wear self-contained breathing apparatus for firefighting if necessary.
Further information	Use water spray to cool unopened containers.

SECTION 6: ACCIDENTAL RELEASE MEASURES		
Personal precautions, protective equipment and emergency procedures	Avoid breathing mist or vapors. Wear respiratory protection. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapor accumulation in low-lying areas.	
Environmental precautions	Prevent further leakage or spillage, if practical and safe. Do not apply water to the spill. Do not allow product to enter drains. Avoid discharge into the environment.	
Methods and materials for containment and remediation	Stop leak if possible and safe. Cover spill with vermiculite, perlite or ground clay. Do not use combustible material such as saw dust. Sweep up and store in appropriate waste container for disposal via a licensed waste disposal company.	

SECTION	7. HAND	LING AND	STORAGE
SECTION	/: DANU	LIING AIND	SIURAGE

Precautions for safe	This material is flammable:
handling:	Avoid vapor formations and use with adequate ventilation, avoid breathing fumes. Vapors are heavier than air and will tend to collect in low areas. Avoid use in confined spaces. Flammable vapors may form explosive mixtures in the air. Ground coating equipment and containers at all times. Use non sparking tools. Isolate, vent, drain, wash and purge systems or equipment before maintenance or repair. Avoid bodily contact with material: Wear appropriate personal protective equipment. Avoid contact with skin and eyes. Wash hands thoroughly after handling and avoid contact with eyes. No eating, drinking or smoking near areas where substance is handled, processed or stored.
Conditions for safe	Keep container clearly labeled and tightly closed in a cool, dry, well-ventilated
storage, including	area. Opened containers must be carefully resealed and kept upright to prevent
incompatibilities	leakage. Keep away from heat, flames, static electricity. Containers are hazardous when empty as they contain product residues. Ventilate closed areas. Keep out of reach of children.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Control: Adequate room ventilation plus local exhaust at points of emission to maintain levels of airborne contaminates below exposure limits. Assure ACGIH TWA and OSHA PEL limits (varies by product) are maintained. Use of fume hoods or closed booths required when product is used in a manner that may generate mist or aerosol

Personal Protective Equipment:

Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times. Solvent resistant (neoprene, nitrile or other nonporous) recommended.

Eyes: Chemical splash goggles should be worn at a minimum.

Skin: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Apron and protective industrial coating recommended.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES			
Appearance:	Colored liquid	Evap. Rate:	Not Available
Physical state:	Liquid	Decomp Temp:	Not Available
Spec Grav./Density:	1.0-1.4 g/cm3	Odor:	Organic solvent
Viscosity:	50-100 Cp	Solubility:	Not Available
Boiling Point:	124-126C	Freezing/Melting pt.:	Not Available
Flammability:	Flammable	Flash Point:	>23C (>73F), closed cup
Partition Coefficient	Not Available	Vapor Density:	Not Available
Vapor Pressure	Not Available	VOC:	Exempt
pH:	N/A	Auto-ignition Temp:	>500C (932F)
		UFL/LFL:	0.9v/v%-10.5v/v%

SECTION 10: STABILITY AND REACTIVITY

Hazardous polymerization	No	
Hazardous Decomposition	Thermal decomposition products include oxides of carbon. Contact with acids and alkalis may release hydrogen.	
Materials to avoid	Strong oxidizers, acids, water and alkalis	
Chemical stability	Stable	

SECTION 11: TOXICOLOGICAL INFORMATION

NTP Carcinogen: No IARC Monographs: No OSHA Regulated: Yes (5mg/m3, 8hTWA) *No components* are recognized as carcinogens by the National Toxicology Program (NTP), the International Agency for Cancer Research (IARC) or the Occupational Safety and Health Administration (OSHA). Reported Human Effects: No human studies have been conducted with this material. The use of recommended protective equipment should minimize any adverse effects.

Based on sums of components, following animal effects are expected:

Oral LD50, rat: >2000 mg/kg Vapor LC50, rat 200 g/m3 Skin irritation, rabbit; corrosive.

SECTION 12: ECOLOGICAL INFORMATION

Avoid disposal in Landfills and sewage systems. Avoid releases into water sources

SECTION 13: DISPOSAL CONSIDERATIONS

This product, as well as any materials impregnated or infused with it during its use, must be disposed of in accordance with all applicable local, state and federal regulations. Contact a licensed professional waste disposal service to dispose of this material

SECTION 14: TRANSPORT INFORMATION

UN 3469 (Paint, flammable, corrosive)

US DOT and IATA

Proper Shipping Paint, flammable, corrosive

Hazard Class: 3[8] UN Number 3469 Packing Group: III

SECTION 15: REGULATORY INFORMATION				
Component	CAS#	Wt%	Regulations	
Proprietary		20-50	TSCA, PA, M, NJ	
Inorganic pigments		15-30	TSCA	
parachlorobenzotrifluoride	98-56-6	20-65	TSCA(export notification), NJ, PA,	
			CA prop. 65	

PA = PA Right-To-Know List of Hazardous Substances

M=Massachusetts Right-To-Know List of Hazardous Substances

NJ= New Jersey Right-To-Know List of Hazardous Substances

DE= Delaware Right-To-Know List of Hazardous Substances

NY= New York Right-To-Know List of Hazardous Substances

PA= Pennsylvania Right-To-Know List of Hazardous Substances

RI= Rhode Island Right-To-Know List of Hazardous Substances

WI= Wisconsin Right-To-Know List of Hazardous Substances

CA Prop. 65 = Safe Drinking Water and Toxic Enforcement Act

TSCA = Toxic Substances Control Act

The following are on California Prop65 list:

Para chlorobenzotrifluoride

Covaron coatings meet all air quality and regulatory requirements with respect to manufacturing and application. Specifically, the hardened finished product does not release any "volatile organic compounds" (VOC) under any ambient conditions.

U.S. TOXIC SUBSTANCES CONTROL ACT: All components of this product are on the TSCA Inventory or are exempt from the TSCA Inventory requirements under 40 CFR 720.30.

This compound is subject to TSCA 12b export notification requirement 475645-84-2

SECTION 16: OTHER INFORMATION

NFPA

Health=3

Fire=3

Reactivity=1

Specific Hazard=No

HMIS

Health=3

Fire=3

Physical Hazard=1

PPE: G- Safety Glasses, Gloves, Vapor respirators

OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of hazard communication program including labeling, material safety data sheets, training and access to written records. We request that you (as it is your legal duty to) make all information in this Safety Data Sheet available to all your employees.

This document and its contents are copyright 2024 Covaron Advanced Materials. License granted to make unlimited copies for internal use, subject to the terms of all applicable confidentiality and non-disclosure agreements. Information contained in this literature is offered for use by technically qualified personnel at their own discretion and risk. All statements and information contained herein are provided in good faith. While based on analytic procedures believed to be reliable, Covaron makes no express or implicit guarantee regarding their accuracy or completeness. As Covaron exercises no control over the end use of the product described herein, it assumes no liability for loss or damage incurred therefrom.