



Health	2
Fire	2
Reactivity	0
PPE	G



# **SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION**

**Product Name**: Covaron InfernoWare™ Coating HDC-2 **Supplier Information**: 1-734-315-4221

Application: Thermosetting amorphous ceramic compoundCovaron Advanced MaterialsCAS#: Not available4401 Varsity Dr, Suite ARTECS: Not availableAnn Arbor, MI 48108

 Document Revision: 1.3
 CHEMTREC (24-hour):
 1-800-424-9300

 Document Revision Date: 2024 July 1
 Poison Control (24-hour):
 1-800-222-1222

For non-emergency assistance: 1-734-315-4221

# SECTION 2: HAZARDS IDENTIFICATION

# GHS classification in accordance with 29 CFR 1910 (OSHA HCS)

Physical - Flammable Liquids (4) Health - Acute toxicity (4 Oral) Skin Corrosion 2

Skin Sensitization 1
Serious Eye damage 2A

Signal word Warning

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

MAZARDS IDENTIFICATION					
GHS haz	ard statements				
H302	Harmful if swallowed				
H315	Cause skin irritation				
H317	May cause an allergic skin reaction				
H319	Cause serious eye irritation				
H334	Respiratory sensitization				
H336	May cause drowsiness or dizziness				
GHS					
precau					
tionar					
У					
statem					
ents					
P201	Obtain special instructions before use.				
P210	Avoid heat/sparks/open flames/hot surfaces.				
P261	Avoid breathing fumes, mist, and vapor.				
P270	Do not eat, drink or smoke when using this product.				
P271	Use only outdoors or in a well-ventilated area.				
P272	Contaminated work clothing must not be allowed				
	out of the workplace.				
P280	Wear protective gloves/protective clothing/eye				
	protection/face protection.				
P284 Wear respiratory protection.					
P301	IF SWALLOWED: Call a POISON CENTER/doctor if				
P312	you feel unwell. Rinse mouth.				
P330					

P302	IF ON SKIN (or hair): remove immediately all
P361	contaminated clothing. Rinse skin with water or
P352	shower.
P305	
	IF IN EYES: Rinse cautiously with water for several
P338	minutes. Remove contact lenses, if present and
P351	easy to do. Continue rinsing. Immediately call a
	POISON CENTER/doctor.
P314	Get medical advice/attention if you feel unwell.
P333	If skin irritation or rash occurs: Get medical
P313	advice/attention.
P363	Wash contaminated clothing before use.
P370	In case of fire: Use sand or carbon dioxide or
P378	powder extinguisher for extinction.
P403	Store locked up in a well-ventilated place.
P235	Keep Cool
P501	Dispose of contents and containers to an approved
	facility in accordance with local, regional, national,
	and international regulations.

SECTION 3: Composition			
Name CAS# Wt%			
Proprietary resin	_	5-40	
Parachlorobenzotrifluoride	98-56-6	20-65	

SECTION 4: FIRST AID MEASURES				
General	Consult a physician. Provide this data sheet to medical personnel. Move out of dangerous area.			
If inhaled	Move person to fresh air. Seek medical attention. If not breathing or unconscious, provide artificial respiration. Exercise caution if performing mouth-to-mouth resuscitation for persons who have inhaled toxic substances.			
Skin Contact	Immediately flush skin with large amount of water while removing contaminated clothing and shoes. Wash off with soap and water for at least 15 minutes. If symptoms persist, seek medical attention. Do not peel solidified product off the skin.			
Eye Contact	Rinse thoroughly with plenty of water or saline solution for at least 15 minutes, occasionally lifting the upper and lower lid. Remove contact lenses if present and easy to do. Continue rinsing. Consult a physician.			
Ingestion	To prevent aspiration of material into the lungs, lay the victim on one side with head lower than the waist. Never give anything by mouth to an unconscious person. Rinse mouth with water, then drink a lot of water. Remove denture if present. Seek medical advice.			

Extinguishing media	Suitable methods of extinction: Use only sand, dry chemical or carbon dioxide.  Unsuitable methods of extinction: Water jets streams may spread the fire.			
Special hazards	Flammable liquid and vapor! Vapors are heavier than air and can travel along the ground to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas. Liquid will float and may reignite on the surface of water.			
Advice for firefighters	Wear self-contained breathing apparatus for firefighting if necessary.			
Further information Use water spray to cool unopened containers.				

SECTION 6: ACCIDENTAL RELEASE MEASURES			
Personal precautions, protective equipment and emergency procedures	Avoid breathing mist or vapors. Wear respiratory protection. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapor accumulation in low-lying areas.		
Environmental precautions	Prevent further leakage or spillage, if practical and safe. Do not allow product to enter drains. Avoid discharge into the environment.		
Methods and materials for containment and remediation	Stop leak if possible and safe. Cover spill with vermiculite, perlite or ground clay.  Do not use combustible material such as saw dust. Sweep up and store in appropriate waste container for disposal via a licensed waste disposal company.		

SECTION 7: HANDLING AND STORAGE					
Precautions for safe This material is flammable:					
handling:	Avoid vapor formations and use with adequate ventilation, avoid breathing fumes. Vapors are heavier than air and will tend to collect in low areas. Avoid use in confined spaces. Flammable vapors may form explosive mixtures in the air. Ground coating equipment and containers at all times. Use non sparking tools. Isolate, vent, drain, wash and purge systems or equipment before maintenance or repair.  Avoid bodily contact with material:  Wear appropriate personal protective equipment. Avoid contact with skin and eyes. Wash hands thoroughly after handling and avoid contact with eyes.				
No eating, drinking or smoking near areas where substance is handle or stored.					
Conditions for safe storage, including incompatibilities	Keep container clearly labeled and tightly closed in a cool, dry, well-ventilated area. Opened containers must be carefully resealed and kept upright to prevent leakage. Keep away from heat, flames, static electricity. Containers are hazardous when empty as they contain product residues. Ventilate closed areas. Keep out of reach of children.				

# **SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Engineering Control**: Adequate room ventilation plus local exhaust at points of emission to maintain levels of airborne contaminates below exposure limits. Assure ACGIH TWA and OSHA PEL limits (varies by product) are maintained. Use of fume hoods or closed booths required when product is used in a manner that may generate mist or aerosol.

# **Personal Protective Equipment:**

**Hands**: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times. Solvent resistant (neoprene, nitrile or other nonporous) recommended.

**Eyes**: Chemical splash goggles should be worn at a minimum.

**Skin:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Apron and protective industrial coating recommended.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES					
Appearance:	Dark liquid	Evap. Rate:	0.9		
Physical state:	Liquid	Decomp Temp:	124 °C where does this come		
			from		
Density:	0.8 - 1.4 g/cm <sup>3</sup>	Odor:	Organic solvent		
Viscosity:	50-100 Cp	Solubility:	negligible		
Boiling Point:	>136 °C	Freezing/Melting pt.:	Not Available		
Flammability:	nmability: Flammable	Flash Point:	43 °C, closed cup		
Partition Coefficient	Not Available	Vapor Density:	6.2		
Vapor Pressure	Not Available	VOC:	Exempt		
pH:	N/A	Auto-ignition Temp:	>500C (932F)		
		UFL/LFL:	0.9v/v%-10.5v/v%		

Section 10.57/DEET / AND REACTION				
Hazardous No polymerization				
Hazardous Thermal decomposition products include oxides of carbon.  Decomposition				
Materials to avoid	Strong oxidizers			
Chemical stability	Stable			

**SECTION 10: STABILITY AND REACTIVITY** 

SECTION 11: TOXICOLOGICAL INFORMATION						
NTP Carcinogen: No	IARC Monographs: No	OSHA Regulated: Yes (5mg/m3, 8hTWA)				

No components are recognized as carcinogens by the National Toxicology Program (NTP), the International Agency for Cancer Research (IARC) or the Occupational Safety and Health Administration (OSHA). Reported Human Effects: No human studies have been conducted with this material. The use of recommended protective equipment should minimize any adverse effects.

Based on sums of components, following animal effects are expected:

Oral LD50, rat: 1000 mg/kg

#### **SECTION 12: ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

**Acute and prolonged toxicity to fish**: LC50 Lepomis macrochirus(Bluegill) 9h 5.6mg/l **Toxicity to aquatic invertebrates** EC50 Daphnia magna (water fleas) 48h 3.7-5.6mg/L

Avoid disposal in Landfills and sewage systems. Avoid releases into water sources

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

This product, as well as any materials impregnated or infused with it during its use, must be disposed of in accordance with all applicable local, state and federal regulations. Contact a licensed professional waste disposal service to dispose of this material

#### **SECTION 14: TRANSPORT INFORMATION**

UN number: not subject to transport regulations

US DOT and IATA
Proper Shipping n/a
Hazard Class: none
UN Number n/a
Packing Group: n/a

Environmentally hazardous substance (aquatic environment) p-chlorobenzotrifluoride

#### **Remarks**

Covaron HDC2 is not subject to transportation regulations as the mixture does not sustain combustion. Per 49 CFR § 173.120(a)(3) of the hazardous materials regulations, liquids with a flash point greater than 35°C that do not sustain combustion according to ASTM D 4206 do not meet the definition of a Class 3 Flammable Liquid. International Air Transport Association (IATA) Dangerous Goods Regulations section 3.3.1.3(a) states that liquids which do not sustain combustion "need not be considered as flammable" if the liquid has "passed a suitable test for combustibility" as prescribed by the UN Manual of Tests and Criteria, Part III, subsection 32.5.2. ASTM D 4206 standards are identical to the UN Manual standards; it is thus considered to be a suitable test for combustibility. Since HDC1 does not sustain combustion when testing with ASTM D 4206, Covaron HDC1 is not considered regulated for purposes of transportation.

# Remarks

p-Chlorobenzotrifluoride (PCBTF) will preferentially partition to the atmosphere, due to its high volatility. It has been estimated that 99.93% of a 100 Kg spill would end up in the atmosphere, while only 0.06% would partition to water

(M. Garlanda, 1990). The aqueous solubility of PCBTF (29.1 mg/L) would also tend to limit its potential impact to exposed aquatic systems. PCBTF has exhibited significant toxicity to aquatic species under laboratory conditions but is unlikely to exhibit a similar degree of acute toxicity under environmental conditions due to the aforementioned solubility and volatility issues. The moderate level of bioaccumulation measured in laboratory tests will also be subject to environmental mitigation due to PCBTF's physical/chemical properties. PCBTF should rapidly volatilize from dry and moist soils. Volatility, and relative environmental partitioning characteristics, make it unlikely that PCBTF represents a significant threat to aquatic or terrestrial environments.

SECTION 15: REGULATORY INFORMATION			
Component	CAS#	Wt%	Regulations
Proprietary resin	_	5-40	TSCA, PA, M, NJ
parachlorobenzotrifluoride	98-56-6	20-65	TSCA(export notification), NJ, PA,
			CA prop. 65

PA = PA Right-To-Know List of Hazardous Substances

M=Massachusetts Right-To-Know List of Hazardous Substances

NJ= New Jersey Right-To-Know List of Hazardous Substances

DE= Delaware Right-To-Know List of Hazardous Substances

NY= New York Right-To-Know List of Hazardous Substances

PA= Pennsylvania Right-To-Know List of Hazardous Substances

RI= Rhode Island Right-To-Know List of Hazardous Substances

WI= Wisconsin Right-To-Know List of Hazardous Substances

CA Prop. 65 = Safe Drinking Water and Toxic Enforcement Act

TSCA = Toxic Substances Control Act

The following are on California Prop65 list:

Para chlorobenzotrifluoride

Covaron coatings meet all air quality and regulatory requirements with respect to manufacturing and application. Specifically, the hardened finished product does not release any "volatile organic compounds" (VOC) under any ambient conditions.

U.S. TOXIC SUBSTANCES CONTROL ACT: All components of this product are on the TSCA Inventory or are exempt from the TSCA Inventory requirements under 40 CFR 720.30.

This compound is subject to TSCA 12b export notification requirement 475645-84-2

# **SECTION 16: OTHER INFORMATION**

#### **NFPA**

Health=2

Fire=2

Reactivity=0

Specific Hazard=No

#### **HMIS**

Health=2

Fire=2

Physical Hazard=0

PPE: G- Safety Glasses, Gloves, Vapor respirators

OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of hazard communication program including labeling, material safety data sheets, training and access to written records. We request that you (as it is your legal duty to) make all information in this Safety Data Sheet available to all your employees.

This document and its contents are copyright 2024 Covaron Advanced Materials. License granted to make unlimited copies for internal use, subject to the terms of all applicable confidentiality and non-disclosure agreements. Information contained in this literature is offered for use by technically qualified personnel at their own discretion and risk. All statements and information contained herein are provided in good faith. While based on analytic procedures believed to be reliable, Covaron makes no express or implicit guarantee regarding their accuracy or completeness. As Covaron exercises no control over the end use of the product described herein, it assumes no liability for loss or damage incurred therefrom.